

# SLM Performer Series



Barco Events

**BARCO**



	<b>G 10</b>	<b>R 10</b>
• Light Output (ANSI)*	10000	10000
• Resolution	1024 x 768 (native) 1600 x 1200 (max)	1280 x 1024 (native) 1600 x 1200 (max)
• Contrast Ratio - full field, standard (high)	500 : 1 (1000 : 1)	800 : 1 (1600:1)
• Brightness Uniformity	90%	90%
• Lamp Power	2.2 kW	2.2 kW
• Lamp Lifetime (max)	1000 Hrs	1000 Hrs
• Lamp Lifetime (typ)	500 Hrs	500 Hrs
• Noise Level (dba) 20°C (68°F)	< 56	< 56
40°C (104°F)	< 58	< 58
• Max. Ambient Temp	35°C (95F)	35°C (95F)
• Seamless Switching	Standard	Standard
• ScenergiX	Standard	Standard
• Network Connection	Optional	Optional
• Mains Voltage	200-240 V	200-240 V
• Fixed Inputs	5 BNC (2x) multistandard / DVI	
• Modular Digital Inputs	2 Slots (equipped with 1 SDI input standard )	
• Power Consumption	2750 W	2750 W
• Weight (including rigging gear)	57 kg (126 lbs)	57 kg (126 lbs)
• <b>Ordering Information</b>		
• Projector Body	R9001000	R9001010
• Spare Lamp (including housing)		R9841810
• Refurb Lamp (returned housing)		R9841820
• Video Input with Decoder		R9841170
• SDI Input Card		R9840110
• HDSDI Input Card		R9840450
• Lenses		
• TLD (0.8)		R9840900
• TLD (1.2)		R9840770
• TLD (1.6 - 2.0)		R9840670
• TLD (2.0 - 2.8)		R9840680
• TLD (2.8 - 5.0)		R9840690
• TLD (5.0 - 8.0)		R9840910

\* Measured with TLD 1.2:1, on axis at 220 V

• Dimensions

