



SLM R12+ Performer specifications

Light output (1)	11,500 Ansi
Resolution	1,400 x 1,050 (native)
Contrast ratio (2)	1,250:1 (full field)
High Contrast Mode (3) (4)	1,700:1 (full field)
Lamp	2.2kW Xenon
Lamp lifetime (maximum)	1,200 Hrs
Lamp lifetime (typical)	800 Hrs
Lamp lifetime (minimum)	500 Hrs
Warranty universal lamphouse	1,000 Hrs
Max. ambient temperature	35°C (95°F)
Power consumption	2,750W
Mains voltage	200 240 V
Weight	56 kg (124 lbs)
Dimensions (W x L x H)	585 x 876 x 429 mm (23.0 x 34.5 x 16.9 inch)
FEATURES	
Scenergix	standard horizontal & vertical electronic edge blending
Network connectivity	optional (10 baseT)
Advanced picture in picture	2 sources simultaneous
INPUTS	
Input source compatibility (5)	1,600 x 1,200 (max. input)
Fixed inputs (standard)	2x configurable 5 cable (BNC) (incl. 2 video decoders) • 2x DVI
Modular inputs	1x SDI (+ loop through) (standard) • 1x HDSDI (+ loop through) (optional)
ORDER INFORMATION	
Projector	R9010171
Spare lamp	R9841810
<i>throw ratio on SLM R12+ Performer</i>	
Fixed focal lenses	TLD HB 0.8 0.75 R9842040
	TLD 1.2 1.1 R9840770
Zoom lenses	TLD HB 1.6 2.0 1.45 1.85 R9842060
	TLD HB 2.0 2.8 1.85 2.55 R9842080
	TLD HB 2.8 5.0 2.55 4.55 R9842100
	TLD HB 5.0 8.0 4.55 7.3 R9842120
Dust filters	dense, high quality microfilters available as spare kit, in a 6pack & 24pack
	6pack R8454096K
	24pack R84540924K